

Double throttle check valve, sea water resistant Type Z2FS 22 -3X...J

Nominal size 25

Series 3X

Features of the sea water resistant version

When compared to the standard version the following modifications have been carried out:

- The external metal components, housing and plug, have been zinc galvanised or given an anti-protection protection.
- The adjustment is protected against corrosion by a cap.
- Sea water resistance is identified by the code „J“ in the ordering code.

Note:

Valve fixing screws must be ordered separately.

6 off M14, DIN 912-10.9 NEL¹⁾; $M_A = 205 \text{ Nm}$; order in clear text, length details as required.

¹⁾ The code „NEL“ stands for „non-electrolytically applied zinc coatings“ which contain a lubrication additive for the reduction of friction in accordance with ISO/WD 10683. Colour: silver.

Further information can be obtained from the standard documentation RE 27 536.

Ordering details, preferred types

Z2FS	22-3X /	J	V	*	
Double throttle check valve	= 22	J =	V =	No code =	NBR seals
Nominal size 25	= 22	J =	V =	V =	FKM seals
Series 30 to 39 (30 to 39: unchanged installation and connection dimensions)	= 3X	S =	S2 =	J =	Sea water resistant
		S =	S2 =		Meter-in control
					Meter-out control

Preferred types	
Type	Material number
Z2FS 22-3X/SJ	00488912
Z2FS 22-3X/S2J	00474737
Z2FS 22-3X/S2JV	00449852

Notes

Mannesmann Rexroth AG
Rexroth Hydraulics

D-97813 Lohr am Main
Jahnstraße 3-5 • D-97816 Lohr am Main
Telefon 0 93 52 / 18-0
Telefax 0 93 52 / 18-23 58 • Telex 6 89 418-0
eMail product.support@rexroth.de
Internet www.rexroth.com

Mannesmann Rexroth Limited

Cromwell Road, St Neots,
Cams, PE19 2ES
Tel: 0 14 80/22 32 56
Fax: 0 14 80/21 90 52
E-mail: info@rexroth.co.uk

The specified data is for product description purposes only and may not be deemed to be guaranteed unless expressly confirmed in the contract.

All rights reserved – Subject to revision
