

Fine throttle, sea water resistant Type F 10 K3...J

Nominal size 10

Series 2X

Features of the sea water resistant version

When compared to the standard version the following modifications have been carried out:

- The external metal components (housing, adjustment element) have been zinc galvanised.
- Sea water resistance is identified by the code „J” in the ordering code.

Note:

Valve fixing screws must be ordered separately:

4 off M5x16, DIN 912-10.9 NEL¹⁾; $M_A = 8,9 \text{ Nm}$, order in clear text.

¹⁾ The code „NEL” stands for „non-electrolytically applied zinc coatings” which contains a lubrication additive for the reduction of friction in accordance with ISO/WD 10683. Colour: silver.

Further information can be obtained from the standard documentation RE 27 761.

Ordering details, preferred types

F	10	K	3	-2X/	J	*
Nominal size 10		= 10			J =	No code = NBR seals V = FKM seals
For manifold mounting		= K			5Q = Orifice 5 Q; progressive 25Q = Orifice 25 Q; progressive	
				2X =		Series 20 to 29

Preferred types	
Type	Material number
F 10 K3-2X/25QJ	00534289
F 10 K3-2X/5QJ	00534288

Notes

Mannesmann Rexroth AG
Rexroth Hydraulics

D-97813 Lohr am Main
Jahnstraße 3-5 • D-97816 Lohr am Main
Telefon 0 93 52 / 18-0
Telefax 0 93 52 / 18-23 58 • Telex 6 89 418-0
eMail product.support@rexroth.de
Internet www.rexroth.com

Mannesmann Rexroth Limited

Cromwell Road, St Neots,
Cams, PE19 2ES
Tel: 0 14 80/22 32 56
Fax: 0 14 80/21 90 52
E-mail: info@rexroth.co.uk

The specified data is for product description purposes only and may not be deemed to be guaranteed unless expressly confirmed in the contract.

All rights reserved – Subject to revision
